

JOB _____ ITEM # _____ QTY # _____



EXTRA LOW, UNDER-COUNTER MODELS

- ONE COMPARTMENT
- OPEN, MODEL D160-23
- OPEN, MODEL D160-33
- ENCLOSED, MODEL D162-23
- ENCLOSED, MODEL D162-33
- HEATED, MODEL DH162-23
- HEATED, MODEL DH162-33

MODEL D162-33



HEIGHT 26" (27" WITH COVERS)

- TWO COMPARTMENT
- OPEN, MODEL D170-23
- OPEN, MODEL D170-33
- ENCLOSED, MODEL D172-23
- ENCLOSED, MODEL D172-33
- HEATED, MODEL DH172-23
- HEATED, MODEL DH172-33

MODEL D172-33

Shown with optional wrap-around bumper.

SPECIFICATIONS

Extra low, under-counter dish carts, one or two compartments, unheated or heated.

CABINET: The cabinet is constructed of all welded 18 ga. stainless steel, with all edges flanged for rigidity. The cabinet includes one or two canted shelves with enclosed ends and full height back at an angle to support dishware, with all interior corners coved to a 1/2" radius. The shelves are set 8" above the floor and are provided with 1/2" diameter holes to permit drainage when the cart is washed.

CASTERS: The unit is mounted on four 4" diameter heavy duty, swivel casters.

MODELS D160 and D170: One or two compartment open carts.


MODELS D162 and D172: Same as Models D160 and D170 except equipped with a 20 ga. stainless steel hinged top cover and with transparent plastic, removable, double sliding doors stacked in vertical tracks and provided with lift handle and latch.

MODELS DH162 and DH172: Same as Models D162 and D172 except equipped with a 120V, single phase, thermostatically regulated heating system complete with a twist lock receptacle and 4' long three wire cord set with NEMA 5-15P plug.


OPTIONS FOR DISH CARTS - EXTRA LOW, UNDER-COUNTER TYPE

- B - Corner bumper
- PB - Perimeter bumper
- Y4 - Polyurethane 4" casters (set of 4)
- Y5 - Polyurethane 5" casters (set of 4)
- WB - Two casters with brakes

MODEL NO.	OVERALL DIMENSIONS			SHELF SIZE	WTS	AMPS	APPROXIMATE CAPACITIES			SHIPPING WEIGHT
	LENGTH	WIDTH	HEIGHT				10" PLATES	7" PLATES	5" PLATES	
<input type="checkbox"/> D160-23	23	16	26	21-3/4x12			96-108	144-162	384-432	65
<input type="checkbox"/> D160-33	33	16	26	31-3/4x12			144-162	192-216	576-648	80
<input type="checkbox"/> D162-23	23	16	27	21-3/4x12			96-108	144-162	384-432	80
<input type="checkbox"/> D162-33	33	16	27	31-3/4x12			144-162	192-216	576-648	105
<input type="checkbox"/> DH162-23	23	16	27	21-3/4x12	250	2.1	96-108	144-162	384-432	95
<input type="checkbox"/> DH162-33	33	16	27	31-3/4x12	500	4.2	144-162	192-216	576-648	120
<input type="checkbox"/> D170-23	23	25	26	21-3/4x10-5/8			192-216	288-324	768-864	85
<input type="checkbox"/> D170-33	33	25	26	31-3/4x10-5/8			288-324	384-432	1152-1296	100
<input type="checkbox"/> D172-23	23	25	27	21-3/4x10-5/8			192-216	288-324	768-864	105
<input type="checkbox"/> D172-33	33	25	27	31-3/4x10-5/8			288-324	384-432	1152-1296	130
<input type="checkbox"/> DH172-23	23	25	27	21-3/4x10-5/8	500	4.2	192-216	288-324	768-864	120
<input type="checkbox"/> DH172-33	33	25	27	31-3/4x10-5/8	750	6.3	286-324	384-432	1152-1296	145



MODEL D160



MODEL D170

Add 2" to length and width for wrap-around bumper.

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.

SPEC E-22

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
 Wausau, WI 54401
 Phone: 800-544-3057
 Fax: 715-842-3125